



QUIK-GEL®

Viscosifier

Description QUIK-GEL is an easy-to-mix, finely ground (200-mesh), premium-grade, high-yielding Wyoming sodium bentonite. QUIK-GEL imparts viscosity, fluid loss control and gelling characteristics to freshwater-based drilling fluids.

Applications/Functions

- Mix with fresh water to form a low-solids drilling fluid for general drilling applications
- Viscosify water-based drilling fluids
- Reduce filtration by forming a thin filter cake with low permeability
- Improve hole-cleaning capability of drilling fluids
- Mix with foaming agents to make "gel/foam" drilling fluids for air/foam drilling applications

Advantages

- NSF/ANSI Standard 60 certified
- Single-sack product and cost effective
- Provides lubricity for drilling fluids
- Mixes easily and quickly reaches maximum viscosity
- Yields more than twice as much mud of the same viscosity as an equal weight of API oilfield grades of bentonite

Typical Properties

- Appearance Grey to tan powder
- Bulk density, lb/ft³ 68 to 72 (compacted)
- pH (3% solution) 8.9

Recommended Treatment

Mix slowly through a jet mixer or sift slowly into the vortex of a high-speed stirrer.

Approximate Amounts of QUIK-GEL Added to Freshwater			
Application/Desired Result	lb/100 gal	lb/bbl	kg/m ³
Normal Drilling Conditions	15-25	6-10	18-30
Unconsolidated Formations	35-50	15-21	42-60
Make-Up For Gel/Foam Systems	12-15	5-7	14-18

- 1 bbl = 42 U.S. gallons

Additional Information

Note:

- For optimum yield, pre-treat make-up water with 1-2 pounds of soda ash per 100 gallons of water (1.2-2.4 kg/m³).

Packaging QUIK-GEL® is packaged in 50-lb (22.7-kg) multiwall paper bags.

Availability QUIK-GEL can be purchased through any Baroid Industrial Drilling Products Retailer. To locate the Baroid IDP retailer nearest you contact the Customer Service Department in Houston or your area IDP Sales Representative.

Baroid Industrial Drilling Products

Product Service Line, Halliburton

3000 N. Sam Houston Pkwy. E.

Houston, TX 77032

Customer Service (800) 735-6075 Toll Free (281) 871-4612

Technical Service (877) 379-7412 Toll Free (281) 871-4613
