

## PART 8 - EARTHING & LIGHTNING PROTECTION

GOOD EARTH

## **GOOD EARTH**



Bentonite and Gypsum mixture to be used in Earthing Installation only and not to be used for any other purpose.

## **PACKAGE SIZE: 15kg**

A 15kg Bag covers approximately 0.03 m<sup>3</sup>

Mixing: Add clean water gradually to mixture and mix slowly until a pourable slurry is achieved.

Normal Mixture: Soil, Clay, Shale, Sandstone, Ironstone - 1 litre Water to 0.5kg GOOD EARTH

Medium Mixture: Saturated (Clay, Shale, Sandstone) Sand – 1 litre Water to 0.8kg GOOD EARTH

Strong Mixture: Gravel or holes with excessive seepage or filled with water – 1 litre Water to 1kg GOOD EARTH

Use mixture within twenty minutes of mixing

Material Safety Data Sheet for Bentonite and Gypsum stipulates the use of Safety Glasses with side shield or Chemical Goggles, (no contact lenses), SAA approved Dust Respirator, Protective Gloves, Safety Footwear and Overalls, when mixing/using Bentonite and Gypsum.

**Disposal:** Bury residue in an authorized landfill.

**Storage:** Keep dry and store in well ventilated area in woven plastic bags. Stacked to prevent sliding or collapse.

For complete Safety Data, consult Appendix B.

FULTON INDUSTRIES AUSTRALIA PTY LTD
TELEPHONE: 61 2 4323 4242 FACSIMILE: 61 2 4322 6197
EMAIL: sales@fultonindustries.com.au